

# 屋内照明器具特性

|         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NTN88006BK                                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LLD2000LCS1 ×1                      580.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0181862(0)DR1                               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4/0.9/BZ3                                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|                |                    |                    |             |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|----------------|--------------------|--------------------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率           | 52%                | 天井                 | 80%         |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|                |                    | 壁                  | 70          | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
|                |                    | 床                  | 10%         |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 上方光束           | 0%                 |                    |             |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
| 下方光束           | 52%                |                    |             |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|                |                    | 室指数                | 照明率 (×0.01) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率            | 良                  | 0.67               | 0.6         | 31 | 25 | 22 | 19  | 31 | 25 | 22 | 19  | 29 | 25 | 21 | 19  | 28 | 24 | 21 | 19  | 18 |
|                | 中                  | 0.63               | 0.8         | 37 | 31 | 28 | 25  | 36 | 31 | 27 | 25  | 35 | 30 | 27 | 25  | 33 | 30 | 27 | 25  | 24 |
|                | 否                  | 0.56               | 1.0         | 40 | 35 | 32 | 29  | 39 | 35 | 31 | 29  | 38 | 34 | 31 | 29  | 37 | 33 | 31 | 29  | 28 |
|                |                    |                    | 1.25        | 43 | 39 | 35 | 33  | 42 | 38 | 35 | 33  | 41 | 37 | 35 | 33  | 40 | 37 | 34 | 32  | 31 |
| 下方投影面積         | c m <sup>2</sup>   |                    | 1.5         | 45 | 41 | 38 | 36  | 44 | 41 | 38 | 36  | 43 | 40 | 37 | 35  | 42 | 39 | 37 | 35  | 34 |
| 等価発光面積         | c m <sup>2</sup>   |                    | 2.0         | 48 | 45 | 42 | 40  | 47 | 44 | 42 | 40  | 46 | 43 | 41 | 39  | 44 | 42 | 40 | 39  | 38 |
| 取付高さ           | 器具間隔最大限            |                    | 2.5         | 49 | 47 | 44 | 42  | 49 | 46 | 44 | 42  | 47 | 45 | 43 | 42  | 46 | 44 | 43 | 41  | 40 |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0         | 50 | 48 | 46 | 44  | 50 | 48 | 46 | 44  | 48 | 47 | 45 | 44  | 47 | 46 | 44 | 43  | 42 |
| H <sub>m</sub> | 1.26H <sub>m</sub> | 1.26H <sub>m</sub> | 4.0         | 52 | 50 | 48 | 47  | 51 | 49 | 48 | 47  | 50 | 48 | 47 | 46  | 48 | 47 | 46 | 45  | 44 |
|                |                    |                    | 5.0         | 53 | 51 | 50 | 49  | 52 | 51 | 49 | 48  | 51 | 49 | 48 | 47  | 49 | 48 | 48 | 47  | 45 |
|                |                    |                    | 7.0         | 54 | 52 | 51 | 50  | 53 | 52 | 51 | 50  | 52 | 51 | 50 | 49  | 50 | 50 | 49 | 48  | 47 |
|                |                    |                    | 10.0        | 54 | 53 | 53 | 52  | 54 | 53 | 52 | 52  | 52 | 52 | 51 | 51  | 51 | 51 | 50 | 50  | 48 |

