

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XL573PFVE                    |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_4850 x1 4850.0 1m |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0175157(0)DB1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/0.7/BZ4                  |  |  |  |  |  |  |  |  |  |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |     |    |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 99%     | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0%  |    |
|        |         | 壁               | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%      | 床               | 10%           |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 99%     | 室指数             | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.81            | 0.6           | 58  | 46  | 38  | 33  | 56  | 45  | 38  | 33  | 54  | 44 | 38 | 33  | 52 | 43 | 37 | 33  | 31 |
|        | 中       | 0.77            | 0.8           | 68  | 57  | 49  | 44  | 66  | 56  | 49  | 43  | 64  | 55 | 48 | 43  | 61 | 53 | 47 | 43  | 41 |
|        | 否       | 0.68            | 1.0           | 74  | 64  | 57  | 51  | 73  | 63  | 56  | 51  | 70  | 62 | 56 | 51  | 67 | 60 | 55 | 50  | 48 |
|        |         |                 | 1.25          | 80  | 71  | 64  | 59  | 79  | 70  | 64  | 59  | 76  | 69 | 63 | 58  | 73 | 67 | 62 | 58  | 55 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 84  | 76  | 70  | 64  | 83  | 75  | 69  | 64  | 80  | 73 | 68 | 64  | 77 | 72 | 67 | 63  | 61 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 90  | 83  | 77  | 73  | 88  | 82  | 77  | 72  | 85  | 80 | 75 | 72  | 83 | 78 | 74 | 71  | 68 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 93  | 87  | 83  | 78  | 92  | 86  | 82  | 78  | 89  | 84 | 80 | 77  | 86 | 82 | 79 | 76  | 73 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 96  | 91  | 86  | 82  | 94  | 90  | 85  | 82  | 91  | 87 | 84 | 81  | 89 | 85 | 82 | 80  | 77 |
| 1.5m   | 1.87m   | 1.88m           | 4.0           | 99  | 95  | 91  | 88  | 97  | 94  | 90  | 87  | 95  | 91 | 89 | 86  | 92 | 89 | 87 | 85  | 82 |
| 2      | 2.49    | 2.49            | 5.0           | 100 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 96  | 94 | 92 | 89  | 94 | 92 | 90 | 88  | 85 |
| 2.5    | 3.08    | 3.08            | 7.0           | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97 | 95 | 93  | 96 | 95 | 93 | 92  | 89 |
| 3      | 3.7     | 3.7             | 10.0          | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 100 | 99 | 98 | 96  | 98 | 97 | 96 | 95  | 92 |

