

屋内照明器具特性	
品番 (品名)	NTN88006BK
光源	LLD3020MLCB1 ×1 715.0 lm
管理番号	K0175527 (0) DR1
BZ分類	BZ1

器具効率		73 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		73 %																							
保守率		良 中 否	0.67	0.6	60	56	53	51	60	55	53	51	59	55	52	51	58	54	52	50	50				
			0.63	0.8	65	60	58	56	64	60	58	56	63	60	57	55	62	59	57	55	54				
			0.56	1.0	67	64	61	59	67	63	61	59	65	63	60	59	64	62	60	58	57				
			1.25	70	66	64	62	69	66	64	62	68	65	63	62	66	64	63	61	60					
下方投影面積		c m ²	1.5	71	68	66	64	70	68	66	64	69	67	65	64	68	66	64	63	62					
等価発光面積			c m ²	2.0	73	71	69	67	72	70	68	67	71	69	68	66	70	68	67	66	64				
取付 高さ	器具間隔最大限		2.5	74	72	71	69	73	72	70	69	72	70	69	68	71	69	68	67	66					
	横方向 (A)		縦方向 (B)	3.0	75	73	72	71	74	73	71	70	73	71	70	69	71	70	69	68	67				
H m	0.41 H m	0.41 H m	4.0	76	75	73	72	75	74	73	72	74	73	72	71	72	71	71	70	68					
			5.0	76	75	74	73	76	75	74	73	74	73	73	72	73	72	71	71	69					
			7.0	77	76	76	75	76	76	75	74	75	74	74	73	73	73	72	72	70					
			10.0	78	77	76	76	77	76	76	75	75	75	74	74	74	73	73	73	71					

