

屋内照明器具特性	
品番 (品名)	NTN88006BK
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 lm
管理番号	K0183945 (0) DR1
BZ分類	BZ2

器具効率		57 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	38	33	29	26	38	32	29	26	36	32	29	26	35	31	28	26	25
			0.63	0.8	44	39	35	33	43	38	35	33	42	38	35	33	41	37	35	33	32
			0.56	1.0	47	43	40	37	47	43	40	37	45	42	39	37	44	41	39	37	36
				1.25	50	46	44	41	50	46	43	41	48	45	43	41	47	44	42	41	40
下方投影面積 等価発光面積		cm ² cm ²		1.5	52	49	46	44	51	48	46	44	50	47	45	43	49	47	45	43	42
				2.0	55	52	50	48	54	51	49	48	53	50	49	47	51	49	48	47	45
				2.5	56	54	52	50	55	53	51	50	54	52	51	49	53	51	50	49	48
				3.0	57	55	53	52	56	54	53	52	55	53	52	51	54	52	51	50	49
H	m	1.15 H	m	1.15 H	m	4.0	58	57	55	54	57	56	55	54	56	55	54	53	52	51	
						5.0	59	58	56	55	58	57	56	55	57	56	55	54	53	52	
						7.0	60	59	58	57	59	58	57	57	58	57	56	56	55	55	53
						10.0	60	60	59	58	60	59	58	58	58	57	57	57	56	56	54

