

# 屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 7				
光源	L L D 2 0 0 0 M L C B 1 × 1                      5 3 1 . 0   l m				
管理番号	K 0 1 7 6 3 4 2 ( 0 ) D R 1				
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2				

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	62 %	室指数	照明率 ( X 0 . 0 1 )																				Z C M
保守率	良	0.63	0.6	4.0	3.4	3.0	2.7	3.9	3.3	2.9	2.7	3.8	3.3	2.9	2.7	3.7	3.2	2.9	2.7	2.5			
	中	0.6	0.8	4.7	4.1	3.7	3.4	4.6	4.0	3.7	3.4	4.4	4.0	3.6	3.4	4.3	3.9	3.6	3.4	3.2			
	否	0.56	1.0	5.1	4.5	4.2	3.9	5.0	4.5	4.1	3.9	4.8	4.4	4.1	3.9	4.7	4.3	4.1	3.8	3.7			
			1.25	5.4	4.9	4.6	4.3	5.3	4.9	4.6	4.3	5.2	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.1			
下方投影面積		cm <sup>2</sup>	1.5	5.6	5.2	4.9	4.6	5.5	5.1	4.9	4.6	5.4	5.0	4.8	4.6	5.2	5.0	4.7	4.5	4.4			
等価発光面積		cm <sup>2</sup>	2.0	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.0	5.6	5.4	5.2	5.0	5.5	5.3	5.1	4.9	4.8			
取付高さ	器具間隔最大限		2.5	6.1	5.8	5.5	5.3	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.3	5.7	5.5	5.3	5.2	5.1			
	横方向 (A)	縦方向 (B)	3.0	6.2	5.9	5.7	5.5	6.1	5.9	5.7	5.5	5.9	5.7	5.6	5.4	5.8	5.6	5.5	5.4	5.2			
H <sub>m</sub>	1.17H <sub>m</sub>	1.17H <sub>m</sub>	4.0	6.3	6.1	6.0	5.8	6.2	6.1	5.9	5.8	6.1	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5			
			5.0	6.4	6.2	6.1	6.0	6.3	6.2	6.0	5.9	6.2	6.0	5.9	5.8	6.0	5.9	5.8	5.8	5.6			
			7.0	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.1	6.0	6.0	5.9	5.8			
			10.0	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.3	6.3	6.3	6.2	6.2	6.2	6.1	6.1	6.0	5.9			

