

# 屋内照明器具特性

品番 (品名)	LGB57582Z				
光源	LDA13L-G/Z100E/S/W ×5      1520.0 l m				
管理番号	K0164510(0)DB1				
BZ分類	BZ6				

器具効率	88%	天井	80%				70%				50%				30%				0%		
	上方光束		22%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		66%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	4.4	3.3	2.6	2.1	4.2	3.1	2.5	2.0	3.7	2.9	2.3	1.9	3.3	2.6	2.1	1.7	1.4	
	中	0.63	0.8	5.2	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.4	3.6	3.0	2.5	3.9	3.2	2.7	2.3	2.0	
	否	0.56	1.0	5.7	4.7	3.9	3.4	5.4	4.4	3.8	3.2	4.8	4.0	3.5	3.0	4.3	3.7	3.2	2.8	2.3	
	下方投影面積		1.25	6.2	5.2	4.5	3.9	5.9	5.0	4.3	3.8	5.2	4.5	4.0	3.5	4.7	4.1	3.6	3.3	2.7	
等価発光面積			1.5	6.5	5.6	4.9	4.4	6.2	5.4	4.8	4.2	5.6	4.9	4.4	3.9	5.0	4.4	4.0	3.6	3.1	
			2.0	7.0	6.3	5.6	5.1	6.7	6.0	5.4	4.9	6.0	5.4	5.0	4.6	5.4	4.9	4.5	4.2	3.6	
取付高さ	器具間隔最大限		2.5	7.4	6.7	6.1	5.6	7.0	6.4	5.9	5.4	6.3	5.8	5.4	5.0	5.7	5.3	4.9	4.6	3.9	
	横方向 (A)	縦方向 (B)	3.0	7.6	7.0	6.5	6.0	7.2	6.7	6.2	5.8	6.5	6.1	5.7	5.3	5.9	5.5	5.2	4.9	4.2	
Hm	1.19Hm	1.18Hm	4.0	7.9	7.4	7.0	6.5	7.5	7.1	6.7	6.3	6.8	6.5	6.1	5.8	6.2	5.9	5.6	5.4	4.6	
			5.0	8.1	7.7	7.3	6.9	7.7	7.3	7.0	6.7	7.0	6.7	6.4	6.2	6.4	6.1	5.9	5.7	4.9	
			7.0	8.3	8.0	7.7	7.4	8.0	7.7	7.4	7.1	7.3	7.0	6.8	6.6	6.6	6.4	6.2	6.1	5.2	
			10.0	8.5	8.3	8.0	7.8	8.2	7.9	7.7	7.5	7.5	7.3	7.1	6.9	6.8	6.7	6.5	6.4	5.5	

