

# 屋内照明器具特性

|         |                   |  |  |  |  |           |  |  |  |  |
|---------|-------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | XND0609WN         |  |  |  |  |           |  |  |  |  |
| 光源      | LED5000_85_620 x1 |  |  |  |  | 620.0 l m |  |  |  |  |
| 管理番号    | K0176487(0)DB1    |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ1               |  |  |  |  |           |  |  |  |  |

|        |               |         |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
|--------|---------------|---------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|
| 器具効率   | 100%          | 天井      | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |     |    |
|        | 上方光束          |         | 0%               | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 0% |
|        | 下方光束          |         | 100%             |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |     |    |
| 室指数    | 照明率 ( X0.01 ) |         |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |    |
| 保守率    | 良             | 0.81    | 0.6              | 73  | 65  | 60  | 56  | 73  | 65  | 59  | 56  | 71  | 64  | 59  | 56  | 69  | 63  | 59  | 56 | 54  |    |
|        | 中             | 0.77    | 0.8              | 82  | 75  | 70  | 66  | 81  | 74  | 70  | 66  | 79  | 73  | 69  | 66  | 78  | 72  | 69  | 66 | 64  |    |
|        | 否             | 0.68    | 1.0              | 88  | 81  | 77  | 73  | 87  | 81  | 76  | 73  | 85  | 79  | 76  | 72  | 83  | 78  | 75  | 72 | 71  |    |
|        |               |         | 1.25             | 92  | 86  | 82  | 79  | 91  | 86  | 82  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 78 | 76  |    |
| 下方投影面積 |               |         | c m <sup>2</sup> |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
| 等価発光面積 |               |         | c m <sup>2</sup> |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
| 取付高さ   | 器具間隔最大限       |         |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
|        | 横方向 (A)       | 縦方向 (B) |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
| H m    | 1.11H m       | 1.11H m | 4.0              | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 96  | 95  | 94 | 92  |    |
|        |               |         | 5.0              | 104 | 103 | 101 | 99  | 103 | 102 | 100 | 98  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96 | 93  |    |
|        |               |         | 7.0              | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98 | 95  |    |
|        |               |         | 10.0             | 106 | 105 | 104 | 104 | 105 | 104 | 103 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99 | 96  |    |

