

屋内照明器具特性	
品番 (品名)	XND0609WW
光源	LED4000_85_615 x1 615.0 l m
管理番号	K0176487(0)DB1
BZ分類	BZ1

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 ( X0.01)																		ZCM																	
下方光束	100%																																																						
保守率	良 中 否	0.81	0.6	73	65	60	56	73	65	59	56	71	64	59	56	69	63	59	56	54																																			
		0.77	0.8	82	75	70	66	81	74	70	66	79	73	69	66	78	72	69	66	64																																			
		0.68	1.0	88	81	77	73	87	81	76	73	85	79	76	72	83	78	75	72	71																																			
			1.25	92	86	82	79	91	86	82	78	89	84	81	78	87	83	80	78	76																																			
下方投影面積		c m <sup>2</sup>		1.5		95		90		86		83		94		89		85		82		91		88		84		82		89		86		83		81		79																	
等価発光面積		c m <sup>2</sup>		2.0		98		94		91		88		97		93		90		88		95		92		89		87		93		90		88		86		84																	
取付高さ	器具間隔最大限		2.5		100		97		94		92		99		96		93		91		97		94		92		90		95		93		91		89		87																		
	横方向 (A)	縦方向 (B)	3.0		102		99		96		94		101		98		95		93		98		96		94		92		96		94		93		91		89																		
H m	1.11H m	1.11H m	4.0		103		101		99		97		102		100		98		97		100		98		97		95		98		96		95		94		92																		
			5.0		104		103		101		99		103		102		100		98		101		100		98		97		99		98		97		96		93																		
			7.0		106		104		103		102		104		103		102		101		102		101		100		99		100		99		98		98		95																		
			10.0		106		105		104		104		105		104		103		103		103		102		102		101		101		100		100		99		96																		

