

屋内照明器具特性

品番 (品名)	XND0679WN															
光源	LED5000_85_615 x1 615.0 l m															
管理番号	K0176095(0)DB1															
BZ分類	BZ1															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
下方光束	100%																				
保守率	良 中 否	0.81	0.6	72	63	57	54	71	63	57	53	69	62	57	53	67	61	57	53	52	
		0.77	0.8	81	73	68	64	80	73	68	64	78	72	67	64	76	71	67	64	62	
			1.0	87	80	75	72	86	79	75	71	84	78	74	71	82	77	74	71	69	
		0.68	1.25	91	86	81	78	90	85	81	77	88	83	80	77	86	82	79	76	75	
下方投影面積	c m ²	1.5	94	89	85	82	93	88	85	82	91	87	84	81	89	85	83	80	79		
		2.0	98	94	90	88	97	93	90	87	95	91	89	86	92	90	87	85	84		
等価発光面積	c m ²	2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89	87		
		3.0	101	99	96	94	100	98	95	93	98	96	94	92	96	94	92	91	89		
取付高さ	器具間隔最大限		4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	94	91	
	横方向 (A)	縦方向 (B)	5.0	104	102	101	99	103	101	100	98	101	99	98	97	99	98	96	95	93	
H m	1.13 H m	1.13 H m	7.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95	
			10.0	106	105	104	103	105	104	103	103	103	102	101	101	100	100	99	99	96	

