

屋内照明器具特性

| | | |
|---------|-------------------|----------|
| 品番 (品名) | XND1037 WY | |
| 光源 | LED2700_85_885 x1 | 885.0 lm |
| 管理番号 | K0176629 (0) DB 1 | |
| BZ分類 | BZ1 | |

| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
|--------|---------|---------------|------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| | | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 上方光束 | 0% | 反射率 | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 下方光束 | 100% | | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.81 | 0.6 | 72 | 63 | 58 | 54 | 71 | 63 | 57 | 54 | 69 | 62 | 57 | 53 | 68 | 61 | 57 | 53 | 52 |
| | 中 | 0.77 | 0.8 | 81 | 74 | 68 | 65 | 80 | 73 | 68 | 65 | 78 | 72 | 68 | 64 | 76 | 71 | 67 | 64 | 63 |
| | 否 | 0.68 | 1.0 | 87 | 80 | 75 | 72 | 86 | 80 | 75 | 72 | 84 | 78 | 74 | 71 | 82 | 77 | 74 | 71 | 69 |
| | | | | 1.25 | 91 | 86 | 81 | 78 | 90 | 85 | 81 | 77 | 88 | 83 | 80 | 77 | 86 | 82 | 79 | 76 |
| 下方投影面積 | | cm^2 | 1.5 | 94 | 89 | 85 | 82 | 93 | 88 | 84 | 81 | 91 | 87 | 83 | 81 | 89 | 85 | 83 | 80 | 78 |
| 等価発光面積 | | cm^2 | 2.0 | 98 | 94 | 90 | 87 | 97 | 93 | 90 | 87 | 94 | 91 | 88 | 86 | 92 | 90 | 87 | 85 | 83 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 100 | 96 | 93 | 91 | 99 | 95 | 93 | 90 | 96 | 94 | 91 | 89 | 94 | 92 | 90 | 88 | 86 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 101 | 98 | 96 | 93 | 100 | 97 | 95 | 93 | 98 | 96 | 93 | 92 | 96 | 94 | 92 | 91 | 88 |
| Hm | 1.21Hm | 1.21Hm | 4.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 100 | 98 | 96 | 95 | 97 | 96 | 95 | 93 | 91 |
| | | | 5.0 | 104 | 102 | 100 | 99 | 103 | 101 | 100 | 98 | 101 | 99 | 98 | 97 | 99 | 97 | 96 | 95 | 93 |
| | | | 7.0 | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99 | 100 | 99 | 98 | 97 | 95 |
| | | | 10.0 | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99 | 99 | 96 |

