

# 屋内照明器具特性

品番 (品名)	NNLK42762J + NNL4300EXJ + FS	
光源	LED5000_85_2160 x1      2160.0 lm	
管理番号	K0132586 (1) DB 1	
BZ分類	BZ2 / 8.5 / BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	100 %		室指数	照明率 ( X0.01 )																ZCM
保守率	良	0.81	0.6	66	56	50	46	65	56	50	45	63	55	49	45	61	54	49	45	44
	中	0.77	0.8	77	69	63	59	76	68	63	58	74	67	62	58	72	66	61	58	56
	否	0.68	1.0	84	77	71	67	83	76	71	67	81	75	70	67	79	73	69	66	65
			1.25	89	83	78	74	88	82	77	74	86	81	77	73	84	79	76	73	71
下方投影面積			1.5	93	87	82	79	91	86	82	78	89	84	81	78	87	83	80	77	75
	等価発光面積		2.0	97	92	88	85	95	91	88	85	93	89	86	84	91	88	85	83	81
取付高さ	器具間隔最大限		2.5	99	95	92	89	98	94	91	89	95	93	90	88	93	91	89	87	85
		横方向 (A)	縦方向 (B)	3.0	101	97	94	92	99	96	94	91	97	95	92	90	95	93	91	89
1.5m	2.11m	2.1m	4.0	103	100	98	96	101	99	97	95	99	97	95	94	97	95	94	92	90
2	2.8	2.65	5.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	95	94	92
2.5	3.5	3.23	7.0	105	104	102	101	104	102	101	100	102	100	99	98	99	98	97	97	94
3	4.18	3.81	10.0	106	105	104	103	105	104	103	102	103	102	101	100	100	100	99	98	96

