

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 7
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 9 1 2 3 9 (1) D R 1
B Z 分類	B Z 1

器具効率		93 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		ZCM
下方光束		93 %																				
保守率		良 中 否	0.67	0.6	79	73	70	67	78	73	70	67	77	72	69	67	76	72	69	67	66	
			0.63	0.8	84	79	76	73	83	79	76	73	82	78	75	73	81	77	75	73	72	
			0.56	1.0	87	83	80	77	86	82	80	77	85	82	79	77	84	81	78	77	75	
				1.25	90	86	83	81	89	86	83	81	88	85	82	80	86	84	82	80	79	
下方投影面積		c m ²		1.5	92	88	86	84	91	88	85	83	89	87	84	83	88	85	84	82	81	
等価発光面積			c m ²	2.0	94	91	89	87	93	91	88	87	91	89	87	86	90	88	86	85	84	
取付 高さ	器具間隔最大限			2.5	95	93	91	89	94	92	91	89	93	91	89	88	91	89	88	87	85	
	横方向 (A)	縦方向 (B)		3.0	96	94	93	91	95	94	92	91	93	92	91	89	92	90	89	88	87	
H m	0.43 H m	0.43 H m		4.0	97	96	95	93	96	95	94	93	95	93	92	91	93	92	91	90	88	
				5.0	98	97	96	95	97	96	95	94	95	94	93	93	93	93	92	91	89	
				7.0	99	98	97	96	98	97	96	96	96	95	95	94	94	93	93	93	90	
				10.0	100	99	98	98	98	98	97	97	96	96	96	95	95	94	94	93	91	

