

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 8
光源	L L D 5 0 0 0 L C C 1 × 1 1 1 4 0 . 0 l m
管理番号	K 0 1 8 7 6 7 5 (2) D R 1
B Z 分類	B Z 2

器具効率		8 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		8 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	5 3	4 6	4 0	3 7	5 3	4 5	4 0	3 7	5 1	4 4	4 0	3 7	5 0	4 4	4 0	3 7	3 5	
			0 . 6 3	0 . 8	6 2	5 5	5 0	4 6	6 1	5 4	5 0	4 6	5 9	5 3	4 9	4 6	5 7	5 2	4 9	4 6	4 4	
			0 . 5 6	1 . 0	6 7	6 1	5 6	5 3	6 6	6 0	5 6	5 3	6 4	5 9	5 5	5 2	6 2	5 8	5 5	5 2	5 1	
			1 . 2 5	7 1	6 6	6 1	5 8	7 0	6 5	6 1	5 8	6 8	6 4	6 0	5 8	6 6	6 3	6 0	5 7	5 6		
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 4	6 9	6 5	6 2	7 3	6 8	6 5	6 2	7 1	6 7	6 4	6 1	6 9	6 6	6 3	6 1	5 9		
			2 . 0	7 7	7 3	7 0	6 7	7 6	7 2	7 0	6 7	7 4	7 1	6 9	6 6	7 2	7 0	6 8	6 6	6 4		
取付 高さ	器具間隔最大限		2 . 5	7 9	7 6	7 3	7 1	7 8	7 5	7 3	7 0	7 6	7 4	7 2	7 0	7 4	7 2	7 0	6 9	6 7		
	横方向 (A) 縦方向 (B)		3 . 0	8 0	7 8	7 5	7 3	7 9	7 7	7 5	7 3	7 8	7 5	7 3	7 2	7 6	7 4	7 2	7 1	6 9		
H m	1 . 2 3 H m	1 . 2 3 H m	4 . 0	8 2	8 0	7 8	7 6	8 1	7 9	7 7	7 6	7 9	7 8	7 6	7 5	7 7	7 6	7 5	7 4	7 2		
			5 . 0	8 3	8 1	8 0	7 8	8 2	8 0	7 9	7 8	8 0	7 9	7 8	7 6	7 8	7 7	7 6	7 5	7 3		
			7 . 0	8 4	8 3	8 2	8 1	8 3	8 2	8 1	8 0	8 1	8 0	7 9	7 9	8 0	7 9	7 8	7 7	7 5		
			1 0 . 0	8 5	8 4	8 3	8 2	8 4	8 3	8 2	8 2	8 2	8 1	8 1	8 0	8 0	8 0	7 9	7 9	7 7		

