

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 5
光源	LLD5000LCC1 ×1 1140.0 l m
管理番号	K0187895 (0) DR 1
B Z 分類	B Z 2

器具効率		8 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		8 9 %	室指数	照明率 (X 0 . 0 1)																	Z C M
保守率		良 中 否	0 . 6 7	0 . 6	6 0	5 1	4 5	4 2	5 9	5 1	4 5	4 2	5 7	5 0	4 5	4 1	5 6	4 9	4 5	4 1	4 0
			0 . 6 3	0 . 8	6 9	6 1	5 6	5 2	6 8	6 1	5 6	5 2	6 6	6 0	5 5	5 2	6 4	5 9	5 5	5 1	5 0
			0 . 5 6	1 . 0	7 5	6 8	6 3	5 9	7 4	6 7	6 2	5 9	7 2	6 6	6 2	5 8	7 0	6 5	6 1	5 8	5 7
				1 . 2 5	7 9	7 3	6 9	6 5	7 8	7 2	6 8	6 5	7 6	7 1	6 7	6 4	7 4	7 0	6 7	6 4	6 2
下方投影面積		cm ²	1 . 5	8 2	7 7	7 2	6 9	8 1	7 6	7 2	6 9	7 9	7 5	7 1	6 8	7 7	7 3	7 0	6 8	6 6	
等価発光面積		cm ²	2 . 0	8 6	8 1	7 8	7 5	8 5	8 1	7 7	7 4	8 2	7 9	7 6	7 4	8 0	7 8	7 5	7 3	7 1	
取付 高さ	器具間隔最大限		2 . 5	8 8	8 4	8 1	7 9	8 7	8 4	8 1	7 8	8 5	8 2	7 9	7 7	8 3	8 0	7 8	7 6	7 4	
	横方向 (A)		縦方向 (B)	3 . 0	9 0	8 6	8 4	8 1	8 8	8 5	8 3	8 1	8 6	8 4	8 2	8 0	8 4	8 2	8 0	7 9	7 7
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	9 1	8 9	8 7	8 5	9 0	8 8	8 6	8 4	8 8	8 6	8 4	8 3	8 6	8 5	8 3	8 2	8 0	
			5 . 0	9 3	9 0	8 9	8 7	9 1	9 0	8 8	8 6	8 9	8 8	8 6	8 5	8 7	8 6	8 5	8 4	8 1	
			7 . 0	9 4	9 2	9 1	9 0	9 3	9 1	9 0	8 9	9 1	8 9	8 8	8 7	8 9	8 8	8 7	8 6	8 3	
			1 0 . 0	9 5	9 4	9 3	9 2	9 4	9 3	9 2	9 1	9 2	9 1	9 0	8 9	9 0	8 9	8 8	8 8	8 5	

