

屋内照明器具特性	
品番 (品名)	LGS9005
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0191301 (1) DR1
BZ分類	BZ1

器具効率 上方光束 下方光束	9 2 % 0 % 9 2 %	天井 壁 床	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
			7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
			1 0 %				1 0 %				1 0 %				1 0 %				0 %	
室指数		照明率 (X 0 . 0 1) Z C M																		
保守率	良	0 . 6 7	0 . 6	8 0	7 6	7 3	7 0	8 0	7 5	7 2	7 0	7 9	7 5	7 2	7 0	7 8	7 4	7 2	7 0	6 9
	中	0 . 6 3	0 . 8	8 5	8 1	7 8	7 6	8 4	8 1	7 8	7 6	8 3	8 0	7 7	7 6	8 2	7 9	7 7	7 5	7 4
	否	0 . 5 6	1 . 0	8 8	8 4	8 2	7 9	8 7	8 4	8 1	7 9	8 6	8 3	8 1	7 9	8 5	8 2	8 0	7 9	7 8
			1 . 2 5	9 0	8 7	8 5	8 3	9 0	8 7	8 4	8 2	8 8	8 6	8 4	8 2	8 7	8 5	8 3	8 1	8 0
下方投影面積 等価発光面積	c m ²		1 . 5	9 2	8 9	8 7	8 5	9 1	8 8	8 6	8 5	9 0	8 7	8 6	8 4	8 8	8 6	8 5	8 3	8 2
	c m ²		2 . 0	9 4	9 2	9 0	8 8	9 3	9 1	8 9	8 8	9 1	9 0	8 8	8 7	9 0	8 8	8 7	8 6	8 5
取付 高さ	器具間隔最大限		2 . 5	9 5	9 3	9 1	9 0	9 4	9 2	9 1	9 0	9 2	9 1	9 0	8 9	9 1	9 0	8 9	8 8	8 6
	横方向 (A)		縦方向 (B)	3 . 0	9 6	9 4	9 3	9 2	9 5	9 3	9 2	9 1	9 3	9 2	9 1	9 0	9 2	9 1	9 0	8 9
H m	0 . 3 4 H m			0 . 3 4 H m	4 . 0	9 7	9 6	9 4	9 3	9 6	9 5	9 4	9 3	9 4	9 3	9 2	9 2	9 2	9 1	9 0
			5 . 0	9 7	9 6	9 6	9 5	9 6	9 6	9 5	9 4	9 5	9 4	9 3	9 3	9 3	9 2	9 2	9 1	8 9
			7 . 0	9 8	9 7	9 7	9 6	9 7	9 6	9 6	9 5	9 5	9 5	9 4	9 4	9 3	9 3	9 3	9 2	9 0
			1 0 . 0	9 9	9 8	9 8	9 7	9 8	9 7	9 7	9 6	9 6	9 5	9 5	9 5	9 4	9 4	9 3	9 3	9 1

