

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 5
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0191284 (1) DR 1
B Z 分類	BZ2 / 1.1 / BZ3

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
			室指数		照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	6 7	5 7	5 0	4 6	6 6	5 6	5 0	4 6	6 4	5 5	5 0	4 6	6 2	5 5	4 9	4 6	4 4
			0 . 6 3	0 . 8	7 6	6 7	6 0	5 6	7 5	6 6	6 0	5 6	7 2	6 5	6 0	5 6	7 0	6 4	5 9	5 5	5 4
			0 . 5 6	1 . 0	8 2	7 3	6 7	6 3	8 0	7 3	6 7	6 3	7 8	7 1	6 6	6 2	7 6	7 0	6 5	6 2	6 0
			1 . 2 5	8 7	7 9	7 3	6 9	8 5	7 8	7 3	6 9	8 3	7 7	7 2	6 8	8 0	7 5	7 1	6 8	6 6	
下方投影面積		c m ²	1 . 5	9 0	8 3	7 8	7 4	8 9	8 2	7 7	7 3	8 6	8 1	7 6	7 3	8 4	7 9	7 5	7 2	7 0	
等価発光面積			c m ²	2 . 0	9 4	8 9	8 4	8 0	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 1	7 8	7 6
2 . 5				9 7	9 2	8 8	8 5	9 6	9 1	8 8	8 4	9 3	8 9	8 6	8 3	9 1	8 8	8 5	8 2	8 0	
取付高さ	器具間隔最大限		3 . 0	9 9	9 5	9 1	8 8	9 8	9 4	9 0	8 8	9 5	9 2	8 9	8 6	9 3	9 0	8 8	8 5	8 2	8 0
	横方向 (A)	縦方向 (B)																			
H m	1 . 1 7 H m	1 . 1 7 H m	4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7	
			5 . 0	1 0 3	1 0 0	9 8	9 5	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	8 9	
			7 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2	
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4	

