

屋内照明器具特性

| | | |
|---------|-------------------|----------|
| 品番 (品名) | XND1038WL | |
| 光源 | LED3000_85_950 ×1 | 950.0 lm |
| 管理番号 | K0176468(0)DB1 | |
| BZ分類 | BZ1 | |

| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
|------|-------------|----------------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| | | | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | | |
| 上方光束 | 0% | 壁 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 下方光束 | 100% | 床 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 | 0.81 0.77 0.68 | 室指数 | | | | | | | | | | | | | | | | | |
| | | | | | | 0.6 | 86 | 80 | 76 | 74 | 85 | 80 | 76 | 74 | 84 | 79 | 76 | 74 | 83 | 78 |
| | | | 0.8 | 91 | 86 | 83 | 81 | 91 | 86 | 83 | 80 | 89 | 85 | 82 | 80 | 88 | 84 | 82 | 80 | 79 |
| | | | 1.0 | 95 | 91 | 87 | 85 | 94 | 90 | 87 | 85 | 93 | 89 | 86 | 84 | 91 | 88 | 86 | 84 | 83 |
| | | | 1.25 | 98 | 94 | 91 | 89 | 97 | 93 | 91 | 88 | 95 | 92 | 90 | 88 | 94 | 91 | 89 | 87 | 86 |
| | | | 1.5 | 100 | 96 | 93 | 91 | 99 | 96 | 93 | 91 | 97 | 94 | 92 | 90 | 95 | 93 | 91 | 90 | 88 |
| | | | 2.0 | 102 | 99 | 97 | 95 | 101 | 98 | 96 | 94 | 99 | 97 | 95 | 94 | 97 | 96 | 94 | 93 | 91 |
| | | | 2.5 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 97 | 100 | 99 | 97 | 96 | 99 | 97 | 96 | 95 | 93 |
| | | | 3.0 | 104 | 102 | 100 | 99 | 103 | 101 | 100 | 98 | 101 | 100 | 98 | 97 | 99 | 98 | 97 | 96 | 94 |
| | | | 4.0 | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99 | 100 | 99 | 98 | 98 | 95 |
| | | | 5.0 | 106 | 105 | 103 | 102 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99 | 99 | 96 |
| | | | 7.0 | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 97 |
| | | | 10.0 | 107 | 107 | 106 | 105 | 106 | 106 | 105 | 104 | 104 | 103 | 103 | 103 | 102 | 102 | 101 | 101 | 98 |

