

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XND1559WN                   |
| 光源       | LED5000_85_1690 x1 1690.0lm |
| 管理番号     | K0176080(0)DB1              |
| BZ分類     | BZ1                         |

|        |                                     |         |             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|-------------------------------------|---------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%                                | 天井      | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|        |                                     | 壁       | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |    |
| 上方光束   | 0%                                  | 床       | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 下方光束   | 100%                                | 室指数     | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良<br>中<br>否<br>0.81<br>0.77<br>0.68 | 0.6     | 72          | 64  | 58  | 54  | 72  | 63  | 58  | 54  | 70  | 63  | 58  | 54  | 68  | 62  | 57  | 54  | 53  |    |
|        |                                     | 0.8     | 82          | 74  | 69  | 65  | 81  | 74  | 69  | 65  | 79  | 73  | 68  | 65  | 77  | 72  | 68  | 65  | 63  |    |
|        |                                     | 1.0     | 87          | 81  | 76  | 73  | 86  | 80  | 76  | 72  | 84  | 79  | 75  | 72  | 82  | 78  | 74  | 72  | 70  |    |
|        |                                     | 1.25    | 92          | 86  | 82  | 79  | 91  | 85  | 81  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 77  | 76  |    |
| 下方投影面積 | cm <sup>2</sup>                     | 1.5     | 95          | 90  | 86  | 83  | 94  | 89  | 85  | 82  | 91  | 87  | 84  | 82  | 89  | 86  | 83  | 81  | 79  |    |
|        |                                     | 2.0     | 98          | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 84  |    |
| 取付高さ   | 器具間隔最大限                             |         | 2.5         | 100 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  |    |
|        | 横方向 (A)                             | 縦方向 (B) | 3.0         | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |
| Hm     | 1.10Hm                              | 1.10Hm  | 4.0         | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94  | 92 |
|        |                                     |         | 5.0         | 104 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |
|        |                                     |         | 7.0         | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 95  |    |
|        |                                     |         | 10.0        | 106 | 105 | 105 | 104 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99  | 96 |

