

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND1509BW                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED4000_85_1600 x1 1600.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0176488(0)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ1                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|------------------|---------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%             | 天井      | 80%             |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|        |                  |         | 壁               | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
| 上方光束   | 0%               | 反射率     | 10%             |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 下方光束   | 100%             |         | 床               | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|        |                  | 室指数     | 照明率 (X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6             | 75  | 67  | 62  | 58  | 74  | 66  | 62  | 58  | 72  | 66  | 61  | 58  | 71  | 65  | 61  | 58  | 56 |
|        |                  | 0.77    | 0.8             | 84  | 77  | 72  | 68  | 83  | 76  | 72  | 68  | 81  | 75  | 71  | 68  | 79  | 74  | 71  | 68  | 66 |
|        |                  |         | 1.0             | 89  | 83  | 79  | 75  | 88  | 82  | 78  | 75  | 86  | 81  | 78  | 75  | 84  | 80  | 77  | 74  | 73 |
|        |                  | 0.68    | 1.25            | 93  | 88  | 84  | 81  | 92  | 87  | 84  | 81  | 90  | 86  | 83  | 80  | 88  | 85  | 82  | 80  | 78 |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 96              | 91  | 87  | 85  | 95  | 90  | 87  | 84  | 93  | 89  | 86  | 84  | 91  | 88  | 85  | 83  | 81  |    |
|        |                  | 2.0     | 99              | 95  | 92  | 90  | 98  | 95  | 92  | 89  | 96  | 93  | 91  | 88  | 94  | 91  | 89  | 88  | 86  |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5             | 101 | 98  | 95  | 93  | 100 | 97  | 95  | 92  | 98  | 95  | 93  | 91  | 96  | 94  | 92  | 90  | 88 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0             | 102 | 100 | 97  | 95  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 95  | 94  | 92  | 90 |
| H m    | 1.10H m          | 1.10H m | 4.0             | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 98  | 101 | 99  | 98  | 96  | 98  | 97  | 96  | 95  | 93 |
|        |                  |         | 5.0             | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 99  | 101 | 100 | 99  | 98  | 99  | 98  | 97  | 96  | 94 |
|        |                  |         | 7.0             | 106 | 105 | 103 | 102 | 105 | 104 | 102 | 101 | 102 | 102 | 101 | 100 | 100 | 100 | 99  | 98  | 96 |
|        |                  |         | 10.0            | 107 | 106 | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 97 |

