

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND1579WL                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED3000_85_1610 x1 1610.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0176095(0)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ1                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |
|--------|------------------|---------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|
| 器具効率   | 100%             | 天井      | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0% |    |    |
|        |                  |         | 反射率              | 壁   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0% |
|        |                  |         |                  | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0% |
| 上方光束   | 0%               | 室指数     | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |
| 下方光束   | 100%             |         |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6              | 72  | 63  | 57  | 54  | 71  | 63  | 57  | 53  | 69  | 62  | 57  | 53  | 67  | 61  | 57 | 53 | 52 |    |
|        |                  | 0.77    | 0.8              | 81  | 73  | 68  | 64  | 80  | 73  | 68  | 64  | 78  | 72  | 67  | 64  | 76  | 71  | 67 | 64 | 62 |    |
|        |                  | 0.68    | 1.0              | 87  | 80  | 75  | 72  | 86  | 79  | 75  | 71  | 84  | 78  | 74  | 71  | 82  | 77  | 74 | 71 | 69 |    |
|        |                  |         | 1.25             | 91  | 86  | 81  | 78  | 90  | 85  | 81  | 77  | 88  | 83  | 80  | 77  | 86  | 82  | 79 | 76 | 75 |    |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 94               | 89  | 85  | 82  | 93  | 88  | 85  | 82  | 91  | 87  | 84  | 81  | 89  | 85  | 83  | 80 | 79 |    |    |
|        |                  | 2.0     | 98               | 94  | 90  | 88  | 97  | 93  | 90  | 87  | 95  | 91  | 89  | 86  | 92  | 90  | 87  | 85 | 84 |    |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 100 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 92  | 90 | 89 | 87 |    |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 101 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 92 | 91 | 89 |    |
| H m    | 1.13H m          | 1.13H m | 4.0              | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96  | 95 | 94 | 91 |    |
|        |                  |         | 5.0              | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 98  | 96 | 95 | 93 |    |
|        |                  |         | 7.0              | 105 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98 | 95 |    |    |
|        |                  |         | 10.0             | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 100 | 99 | 96 |    |    |

