

# 屋内照明器具特性

品番 (品名)	XND2036SN		
光源	LED5000_85_1990 ×1	1990.0lm	
管理番号	K0176631(0)DB1		
BZ分類	BZ1		

器具効率	101%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	101%		室指数	照明率 (X0.01)																ZCM
保守率	良 0.81	0.6	80	73	68	65	79	72	68	65	77	72	68	65	76	71	67	65	63	
	中 0.77		0.8	87	81	77	74	87	81	77	74	85	80	76	74	83	79	76	73	72
	否 0.68		1.0	92	86	82	80	91	86	82	79	89	85	81	79	87	84	81	79	77
下方投影面積	cm <sup>2</sup>	1.25	95	91	87	84	94	90	87	84	93	89	86	84	91	88	85	83	82	
		等価発光面積	1.5	98	94	90	88	97	93	90	87	95	92	89	87	93	90	88	86	85
取付高さ	器具間隔最大限		2.0	101	97	95	92	100	97	94	92	98	95	93	91	96	94	92	90	88
	Hm	0.75Hm	2.5	102	100	97	95	101	99	97	95	99	97	95	94	97	96	94	93	91
Hm		縦方向 (B)	3.0	104	101	99	97	102	100	98	97	100	98	97	95	98	97	95	94	92
	Hm	0.75Hm	4.0	105	103	101	100	104	102	101	99	102	100	99	98	100	98	97	96	94
Hm			5.0	106	104	103	101	105	103	102	101	102	101	100	99	100	99	99	98	95
	Hm		7.0	107	106	104	103	106	104	104	103	103	102	102	101	101	101	100	99	97
Hm			10.0	107	107	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98

