

# 屋内照明器具特性

品番 (品名)	XND1566SW	
光源	LED4000_85_1640 x1	1640.0lm
管理番号	K0176640(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%		
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10			
上方光束	0%	壁	照明率 ( X0.01 )																ZCM		
下方光束	100%	床	照明率 ( X0.01 )																ZCM		
保守率	良	0.81	室指数	0.6	79	72	68	64	79	72	67	64	77	71	67	64	76	70	67	64	63
	中	0.77		0.8	87	81	76	73	86	80	76	73	84	79	76	73	83	78	75	73	71
	否	0.68		1.0	92	86	82	79	91	85	82	79	89	84	81	78	87	83	80	78	77
下方投影面積	cm <sup>2</sup>	1.25	95	90	87	84	94	90	86	84	92	88	86	83	91	87	85	83	81		
		1.5	98	93	90	87	97	93	90	87	95	91	89	86	93	90	88	86	84		
等価発光面積	cm <sup>2</sup>	2.0	100	97	94	92	99	96	94	91	97	95	93	91	95	93	91	90	88		
		2.5	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	92	90		
取付高さ	器具間隔最大限		3.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92	
	横方向 (A)	縦方向 (B)		4.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	96	94
Hm	0.73Hm	0.73Hm	5.0	106	104	103	101	104	103	102	101	102	101	100	99	100	99	98	98	95	
			7.0	107	105	104	103	105	104	103	102	103	102	101	101	100	100	99	99	97	
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98	

