

屋内照明器具特性

品番 (品名)	XND2057WV														
光源	LED3500_85_1940 x1 1940.0lm														
管理番号	K0176634(0)DB1														
BZ分類	BZ1														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	100%																				
保守率	良 中 否	0.81	0.6	72	63	57	53	71	62	57	53	69	61	57	53	67	61	56	53	51	
		0.77	0.8	81	73	68	64	80	73	68	64	78	72	67	64	76	71	67	64	62	
			1.0	87	80	75	71	86	79	75	71	84	78	74	71	82	77	73	71	69	
		0.68	1.25	91	85	81	77	90	85	80	77	88	83	80	77	86	82	79	76	75	
下方投影面積	c m ²	1.5	94	89	85	81	93	88	84	81	91	87	83	81	89	85	82	80	78		
		2.0	98	93	90	87	96	93	89	87	94	91	88	86	92	89	87	85	83		
取付高さ	器具間隔最大限		2.5	100	96	93	91	99	95	93	90	96	94	91	89	94	92	90	88		
	横方向 (A)	縦方向 (B)	3.0	101	98	96	93	100	97	95	93	98	95	93	92	96	94	92	90		
Hm	1.23Hm	1.23Hm	4.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	95	93		
			5.0	104	102	100	99	103	101	99	98	101	99	98	96	98	97	96	95		
			7.0	105	104	102	101	104	103	102	100	102	101	100	99	100	99	98	97		
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99		

