

屋内照明器具特性

品番 (品名)	XND2508BY	
光源	LED2700_85_2140 ×1	2140.0lm
管理番号	K0176483(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.81	0.6	78	71	66	63	77	71	66	63	76	70	66	63	74	69	65	63	61
	中	0.77	0.8	86	80	75	72	85	79	75	72	83	78	74	72	82	77	74	71	70
	否	0.68	1.0	91	85	81	78	90	84	81	78	88	83	80	77	86	82	79	77	76
下方投影面積	等価発光面積	cm ²	1.25	94	90	86	83	93	89	85	83	92	88	85	82	90	86	84	82	80
			1.5	97	93	89	86	96	92	89	86	94	90	88	85	92	89	87	85	83
取付高さ	器具間隔最大限		2.0	100	96	94	91	99	96	93	91	97	94	92	90	95	93	91	89	87
	横方向 (A)	縦方向 (B)	2.5	102	99	96	94	101	98	96	94	99	96	94	93	97	95	93	92	90
Hm	0.74Hm	0.74Hm	3.0	103	100	98	96	102	99	97	96	100	98	96	95	98	96	95	93	91
			4.0	104	101	101	99	103	101	100	98	101	100	98	97	99	98	97	96	93
			5.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96
			10.0	107	106	105	104	106	105	104	104	103	103	102	102	101	101	100	100	97

