

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | XND2536SV          |           |
| 光源      | LED3500_85_2365 ×1 | 2365.0 lm |
| 管理番号    | K0176631(0)DB1     |           |
| BZ分類    | BZ1                |           |

|                  |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |
|------------------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|
| 器具効率             | 101%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |     |
|                  | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0%  |
| 下方光束             | 101%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0%  |
| 室指数              | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |
| 保守率              | 良 0.81          | 0.6     | 80   | 73  | 68  | 65  | 79  | 72  | 68  | 65  | 77  | 72  | 68  | 65  | 76  | 71  | 67  | 65  | 63 |     |
|                  | 中 0.77          |         | 0.8  | 87  | 81  | 77  | 74  | 87  | 81  | 77  | 74  | 85  | 80  | 76  | 74  | 83  | 79  | 76  | 73 | 72  |
|                  | 否 0.68          |         | 1.0  | 92  | 86  | 82  | 80  | 91  | 86  | 82  | 79  | 89  | 85  | 81  | 79  | 87  | 84  | 81  | 79 | 77  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 95   | 91  | 87  | 84  | 94  | 90  | 87  | 84  | 93  | 89  | 86  | 84  | 91  | 88  | 85  | 83  | 82 |     |
|                  |                 | 1.5     | 98   | 94  | 90  | 88  | 97  | 93  | 90  | 87  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 85 |     |
| 取付高さ             | 器具間隔最大限         |         | 2.0  | 101 | 97  | 95  | 92  | 100 | 97  | 94  | 92  | 98  | 95  | 93  | 91  | 96  | 94  | 92  | 90 | 88  |
|                  | 横方向 (A)         | 縦方向 (B) | 2.5  | 102 | 100 | 97  | 95  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 96  | 94  | 93 | 91  |
| Hm               | 0.75Hm          | 0.75Hm  | 3.0  | 104 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94 | 92  |
|                  |                 |         | 4.0  | 105 | 103 | 101 | 100 | 104 | 102 | 101 | 99  | 102 | 100 | 99  | 98  | 100 | 98  | 97  | 96 | 94  |
|                  |                 |         | 5.0  | 106 | 104 | 103 | 101 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 99  | 98 | 95  |
|                  |                 |         | 7.0  | 107 | 106 | 104 | 103 | 106 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 99  | 97 |     |
|                  |                 |         | 10.0 | 107 | 107 | 106 | 105 | 106 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 98 |     |

