

# 屋内照明器具特性

品番 (品名)	XND2558SN	
光源	LED5000_85_2410 ×1      2410.0 lm	
管理番号	K0176473(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%		
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%	
		室指数	照明率 ( X0.01 )																ZCM		
保守率	良	0.81	0.6	77	70	65	61	76	69	65	61	75	68	64	61	73	68	64	61	60	
	中	0.77	0.8	85	79	74	71	84	78	74	70	82	77	73	70	81	76	73	70	69	
	否	0.68	1.0	90	84	80	77	89	84	80	76	87	82	79	76	85	81	78	76	74	
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.25	94	89	85	82	93	88	84	82	91	87	84	81	89	86	83	81	79
				1.5	97	92	88	86	95	91	88	85	93	90	87	85	92	89	86	84	82
取付高さ	器具間隔最大限		Hm	2.5	102	98	96	94	100	98	95	93	98	96	94	92	96	94	93	91	89
	横方向 (A)	縦方向 (B)		3.0	103	100	98	96	102	99	97	95	99	97	96	94	97	96	94	93	91
Hm	0.75Hm	0.75Hm	4.0	104	102	100	99	103	101	100	98	101	99	98	97	99	98	96	95	93	
			5.0	105	103	102	101	104	102	101	100	102	101	99	98	100	99	98	97	94	
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96	
			10.0	107	106	105	104	106	105	104	103	104	103	102	102	101	101	100	100	97	

