

屋内照明器具特性

品番 (品名)	XND2068SW		
光源	LED4000_85_1995 ×1	1995.0lm	
管理番号	K0176476(0)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.81	0.6	85	79	76	73	84	79	75	73	83	78	75	73	82	78	75	73	72	
	中 0.77	0.8	91	86	82	80	90	85	82	80	89	85	82	79	87	84	81	79	78	
	否 0.68	1.0	95	90	87	84	94	90	86	84	92	89	86	84	91	88	85	83	82	
下方投影面積	cm ²	1.25	98	94	91	88	97	93	90	88	95	92	89	87	93	91	89	87	86	
		1.5	99	96	93	91	98	95	93	90	97	94	92	90	95	93	91	89	88	
等価発光面積	cm ²	2.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	92	91	
		2.5	103	101	99	97	102	100	98	96	100	98	97	95	98	97	96	94	92	
取付高さ	器具間隔最大限		3.0	104	102	100	99	103	101	99	98	101	99	98	97	99	98	97	96	94
	横方向 (A)	縦方向 (B)	4.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95
Hm	0.76Hm	0.76Hm	5.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	99	99	96
			7.0	107	106	105	104	106	105	104	103	104	103	102	101	101	100	100	99	97
			10.0	107	107	106	105	106	106	105	104	104	104	103	103	102	102	101	101	98

