

# 屋内照明器具特性

品番 (品名)	XND2068WN	
光源	LED5000_85_2020 ×1      2020.0lm	
管理番号	K0176477(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	101%	床		10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良 0.81	0.6	85	79	75	73	84	79	75	73	83	78	75	72	82	78	75	72	71		
	中 0.77		0.8	91	86	82	79	90	85	82	79	89	84	81	79	87	84	81	79	78	
	否 0.68		1.0	95	90	87	84	94	89	86	84	92	88	86	83	91	87	85	83	82	
下方投影面積	cm <sup>2</sup>	1.25	98	93	90	88	97	93	90	88	95	92	89	87	93	91	88	87	85		
		1.5	99	96	93	91	99	95	93	90	97	94	92	90	95	93	91	89	88		
等価発光面積	cm <sup>2</sup>	2.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	92	91		
		2.5	103	101	99	97	102	100	98	96	100	98	97	95	98	97	96	94	92		
器具間隔最大限	高さ		3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	94		
	横方向 (A)	縦方向 (B)	4.0	106	104	102	101	104	103	102	100	102	101	100	99	100	99	98	95		
Hm	0.75Hm	0.75Hm	5.0	106	105	104	102	105	104	103	102	103	102	101	100	101	100	99	96		
			7.0	107	106	105	104	106	105	104	103	104	103	102	102	101	101	100	97		
			10.0	108	107	106	106	106	105	105	104	104	103	103	102	102	101	101	98		

