

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND1537SV                    |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED3500_85_1580 x1 1580.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0176632(0)DB1               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ1                          |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 器具効率   | 100%             | 天井       | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |    |
|        |                  |          | 壁                | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0% |
| 上方光束   | 0%               | 反射率      | 10%              |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |    |
| 下方光束   | 100%             |          | 床                | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0% |
|        |                  | 室指数      | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
| 保守率    | 良<br>中<br>否      | 0.81     | 0.6              | 75  | 67  | 62  | 58  | 74  | 67  | 62  | 58  | 73  | 66  | 61  | 58  | 71  | 65  | 61  | 58 | 57 |
|        |                  | 0.77     | 0.8              | 84  | 77  | 72  | 69  | 83  | 77  | 72  | 69  | 81  | 76  | 72  | 69  | 80  | 75  | 71  | 68 | 67 |
|        |                  |          | 1.0              | 89  | 83  | 79  | 76  | 88  | 83  | 79  | 76  | 86  | 82  | 78  | 75  | 85  | 80  | 77  | 75 | 73 |
|        |                  | 0.68     | 1.25             | 93  | 88  | 84  | 81  | 92  | 87  | 84  | 81  | 90  | 86  | 83  | 80  | 88  | 85  | 82  | 80 | 78 |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 96               | 91  | 88  | 85  | 95  | 91  | 87  | 85  | 93  | 89  | 86  | 84  | 91  | 88  | 85  | 83  | 82 |    |
|        |                  | 2.0      | 99               | 95  | 92  | 90  | 98  | 95  | 92  | 89  | 96  | 93  | 91  | 89  | 94  | 92  | 90  | 88  | 86 |    |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 101 | 98  | 95  | 93  | 100 | 97  | 95  | 93  | 98  | 95  | 93  | 92  | 96  | 94  | 92  | 91 | 89 |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 102 | 100 | 97  | 95  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 95  | 94  | 92 | 90 |
| H m    | 1.02 H m         | 1.02 H m | 4.0              | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 97  | 100 | 99  | 97  | 96  | 98  | 97  | 96  | 95 | 93 |
|        |                  |          | 5.0              | 105 | 103 | 101 | 100 | 103 | 102 | 101 | 99  | 101 | 100 | 99  | 98  | 99  | 98  | 97  | 96 | 94 |
|        |                  |          | 7.0              | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 100 | 99  | 99  | 98 | 95 |
|        |                  |          | 10.0             | 106 | 105 | 105 | 104 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99 | 97 |

