

# 屋内照明器具特性

|         |                    |  |  |  |  |           |  |  |  |  |
|---------|--------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | XND1039WN          |  |  |  |  |           |  |  |  |  |
| 光源      | LED5000_85_1035 x1 |  |  |  |  | 1035.0 lm |  |  |  |  |
| 管理番号    | K0176070(2)DB1     |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ1                |  |  |  |  |           |  |  |  |  |

|        |                  |         |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|------------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%             | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|        |                  |         | 壁             | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
| 上方光束   | 0%               | 反射率     | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 下方光束   | 100%             |         | 床             | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|        |                  | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6           | 73  | 64  | 59  | 55  | 72  | 64  | 59  | 55  | 70  | 63  | 58  | 55  | 69  | 62  | 58  | 55  | 53 |
|        |                  | 0.77    | 0.8           | 82  | 75  | 70  | 66  | 81  | 74  | 69  | 66  | 79  | 73  | 69  | 65  | 77  | 72  | 68  | 65  | 64 |
|        |                  |         | 1.0           | 88  | 81  | 76  | 73  | 87  | 80  | 76  | 73  | 85  | 79  | 75  | 72  | 83  | 78  | 75  | 72  | 70 |
|        |                  | 0.68    | 1.25          | 92  | 86  | 82  | 79  | 91  | 86  | 82  | 79  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 78  | 76 |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 95            | 90  | 86  | 83  | 94  | 89  | 85  | 82  | 91  | 88  | 84  | 82  | 90  | 86  | 83  | 81  | 79  |    |
|        |                  | 2.0     | 98            | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 84  |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5           | 100 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 87 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0           | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |
| H m    | 1.1H m           | 1.1H m  | 4.0           | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94  | 92 |
|        |                  |         | 5.0           | 104 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |
|        |                  |         | 7.0           | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95 |
|        |                  |         | 10.0          | 106 | 105 | 105 | 104 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99  | 96 |

