

# 屋内照明器具特性

品番 (品名)	XND1507WW	
光源	LED4000_85_1575 x1	1575.0 lm
管理番号	K0176490(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	0%	反射率	床	10%				10%				10%				10%				0%		
下方光束	100%		室指数	照明率 ( X0.01) ZCM																		
保守率	良 中 否 0.81 0.77 0.68	0.6	73	64	58	55	72	64	58	55	70	63	58	54	68	62	57	54	53			
		0.8	82	74	69	65	81	74	69	65	79	73	68	65	77	72	68	65	63			
		1.0	87	81	76	72	86	80	76	72	84	79	75	72	82	78	74	71	70			
		1.25	92	86	82	78	91	85	81	78	88	84	80	77	86	83	79	77	75			
下方投影面積	c m <sup>2</sup>	1.5	94	89	85	82	93	89	85	82	91	87	84	81	89	86	83	81	79			
		2.0	98	94	90	88	97	93	90	87	95	91	89	86	93	90	88	86	84			
取付高さ	器具間隔最大限		2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89	87		
	横方向 (A)	縦方向 (B)	3.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	92	91	89		
H m	1.17H m	1.17H m	4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	94	91		
			5.0	104	102	101	99	103	101	100	98	101	99	98	97	99	98	96	95	93		
			7.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	95			
			10.0	106	105	104	104	105	104	103	103	103	102	101	101	100	100	99	96			

