

屋内照明器具特性

品番 (品名)	NCN25301W														
光源	LED4000_85_2070 x1 2070.0lm														
管理番号	K0177437(0)DB1														
BZ分類	BZ2/0.7/BZ1														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否	0.81	0.6	72	63	57	53	71	62	57	53	69	61	56	53	67	61	56	53	51
		0.77	0.8	81	73	68	64	80	73	68	64	78	72	67	64	76	71	67	64	62
		0.68	1.0	87	80	75	72	86	80	75	71	84	78	74	71	82	77	74	71	69
			1.25	92	86	81	78	90	85	81	78	88	84	80	77	86	82	79	77	75
下方投影面積	c m ²	1.5	94	89	85	82	93	88	85	82	91	87	84	81	89	86	83	80	79	
		2.0	98	94	90	88	97	93	90	87	95	91	89	86	93	90	88	85	84	
取付高さ	器具間隔最大限		2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89	87
	横方向 (A)	縦方向 (B)	3.0	102	99	96	94	101	98	95	93	98	96	94	92	96	94	92	91	89
H m	1.21H m	1.21H m	4.0	103	101	99	97	102	100	98	96	100	98	97	95	98	96	95	94	91
			5.0	105	103	101	99	103	102	100	98	101	100	98	97	99	98	97	96	93
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	98	95	
			10.0	107	106	105	104	105	104	104	103	103	102	102	101	101	100	100	99	96

