

# 屋内照明器具特性

品番 (品名)	P M L E L 1 4 4 5 0 F C										
光源	LED5000_70_3910 x1 3910.0 1 m										
管理番号	K0176993 ( 0 ) DY 1										
BZ分類	BZ5 / 0.7 / BZ4										

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	2 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	98 %		室指数	照明率 ( X0.01 )																ZCM
保守率	良	0.69	0.6	58	46	39	33	57	46	38	33	54	44	38	33	52	43	37	33	31
	中	0.67	0.8	68	57	50	44	67	56	49	44	64	55	48	43	61	53	47	43	41
	否	0.63	1.0	75	65	57	52	73	64	57	51	70	62	56	51	67	60	55	50	48
			1.25	81	72	65	59	79	70	64	59	76	68	63	58	73	67	62	58	55
下方投影面積			1.5	85	76	70	65	83	75	69	64	80	73	68	63	77	71	66	63	60
			2.0	90	83	78	73	88	82	77	72	85	80	75	71	82	77	74	70	67
取付高さ	器具間隔最大限		2.5	93	88	83	78	92	86	82	78	88	84	80	76	85	82	78	75	72
	横方向 (A)	縦方向 (B)	3.0	96	91	86	82	94	89	85	82	91	87	83	80	88	84	81	79	76
1.5m	1.92 m	2.24 m	4.0	99	95	91	88	97	93	90	87	94	91	88	85	91	88	86	84	81
2	2.53	2.77	5.0	100	97	94	91	99	96	93	90	96	93	91	89	93	91	89	87	84
2.5	3.14	3.35	7.0	102	100	98	96	101	99	96	94	98	96	94	92	95	93	92	90	87
3	3.76	3.93	10.0	104	102	101	99	103	101	99	98	100	98	97	96	97	96	94	93	90

