

# 屋内照明器具特性

品番 (品名)	NNN33002W															
光源	LED3500_85_1830 x1 1830.0 lm															
管理番号	K0177078(0)DB1															
BZ分類	BZ2/8.5/BZ1															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 ( X0.01)																ZCM		
下方光束	100%																				
保守率	良 中 否	0.81	0.6	68	58	52	48	67	58	52	48	65	57	52	48	63	56	51	47	46	
		0.77	0.8	78	69	64	59	77	69	63	59	75	68	63	59	73	67	62	59	57	
			1.0	84	77	71	67	83	76	71	67	81	75	70	67	79	73	69	66	65	
		0.68	1.25	89	83	78	74	88	82	77	74	86	80	76	73	84	79	76	73	71	
下方投影面積	c m <sup>2</sup>	1.5	92	87	82	78	91	86	82	78	89	84	81	78	87	83	80	77	75		
		2.0	97	92	88	85	95	91	87	84	93	89	86	84	91	88	85	83	81		
取付高さ	器具間隔最大限		2.5	99	95	92	89	98	94	91	88	95	92	90	87	93	91	88	86	84	
	横方向 (A)	縦方向 (B)	3.0	101	97	94	92	99	96	94	91	97	94	92	90	95	93	91	89	87	
1.5m	1.7m	1.88m	4.0	103	100	98	96	101	99	97	95	99	97	95	94	97	95	94	92	90	
2	2.25	2.34	5.0	104	102	100	98	102	101	99	97	100	99	97	96	98	97	95	94	92	
2.5	2.81	2.82	7.0	105	103	102	101	104	102	101	100	102	100	99	98	99	98	97	97	94	
3	3.35	3.32	10.0	106	105	104	103	105	104	103	102	102	102	101	100	100	100	99	98	96	

