

屋内照明器具特性	
品番 (品名)	XLGE8034
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0190581 (0) DR 1
BZ分類	BZ10

器具効率		5 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		2 7 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		2 7 %																			
保守率		良 中 否	0 . 6 3	0 . 6	2 3	1 6	1 1	8	2 1	1 4	1 0	8	1 7	1 2	8	6	1 3	9	7	5	2
			0 . 6	0 . 8	2 7	2 0	1 6	1 2	2 5	1 9	1 4	1 1	2 0	1 5	1 2	9	1 6	1 2	9	7	3
			0 . 5 6	1 . 0	3 0	2 4	1 9	1 5	2 8	2 2	1 7	1 4	2 2	1 8	1 4	1 2	1 8	1 4	1 1	9	5
			1 . 2 5	3 3	2 7	2 2	1 9	3 0	2 5	2 1	1 7	2 5	2 0	1 7	1 4	2 0	1 6	1 4	1 1	6	
下方投影面積		c m ²	1 . 5	3 6	3 0	2 5	2 1	3 2	2 7	2 3	2 0	2 7	2 2	1 9	1 6	2 1	1 8	1 5	1 3	8	
			等価発光面積	c m ²	2 . 0	3 9	3 3	2 9	2 6	3 5	3 1	2 7	2 4	2 9	2 5	2 2	2 0	2 3	2 0	1 8	1 6
取付 高さ	器具間隔最大限		2 . 5	4 1	3 6	3 2	2 9	3 7	3 3	3 0	2 7	3 1	2 8	2 5	2 2	2 5	2 2	2 0	1 8	1 2	
	横方向 (A) 縦方向 (B)		3 . 0	4 2	3 8	3 4	3 1	3 9	3 5	3 2	2 9	3 2	2 9	2 7	2 4	2 6	2 4	2 2	2 0	1 3	
H m	0 . 0 0 H m	1 . 7 2 H m	4 . 0	4 4	4 1	3 8	3 5	4 1	3 8	3 5	3 2	3 4	3 2	2 9	2 7	2 8	2 6	2 4	2 2	1 5	
			5 . 0	4 5	4 2	4 0	3 7	4 2	3 9	3 7	3 5	3 5	3 3	3 1	2 9	2 9	2 7	2 6	2 4	1 6	
			7 . 0	4 7	4 5	4 2	4 0	4 3	4 1	3 9	3 7	3 7	3 5	3 3	3 2	3 0	2 9	2 8	2 6	1 8	
			1 0 . 0	4 8	4 6	4 5	4 3	4 5	4 3	4 2	4 0	3 8	3 7	3 5	3 4	3 2	3 0	2 9	2 9	2 0	

