

屋内照明器具特性

品番 (品名)	XLGB1136														
光源	LLD2000CU1 x1 566.0 lm														
管理番号	K0179050(0)DR1														
BZ分類	BZ3/4.5/BZ4														

器具効率	80%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	1%	反射率	10%				10%				10%				10%				0%				
下方光束	79%		床	10%				10%				10%				10%				0%			
		室指数	照明率 (X0.01) ZCM																				
保守率	良	0.67	0.6	51	43	38	34	50	43	38	34	49	42	37	34	47	41	37	34	32			
	中	0.63	0.8	59	51	46	42	58	50	45	42	56	49	45	41	54	48	44	41	40			
	否	0.56	1.0	63	56	51	47	62	55	51	47	60	54	50	47	58	53	49	46	45			
			1.25	67	61	56	52	66	60	56	52	64	59	55	52	62	58	54	51	50			
下方投影面積	cm ²	等価発光面積	cm ²	1.5	70	64	60	56	69	63	59	56	67	62	58	55	65	61	57	55	53		
				2.0	74	69	65	62	73	68	64	61	70	67	63	61	68	65	62	60	58		
取付高さ	器具間隔最大限		H _m	1.32H _m	1.32H _m	2.5	76	72	68	65	75	71	68	65	73	69	67	64	71	68	66	63	62
	横方向 (A)	縦方向 (B)				3.0	78	74	71	68	76	73	70	68	74	72	69	67	72	70	68	66	64
						4.0	80	77	74	72	79	76	74	71	76	74	72	70	74	73	71	69	67
						5.0	81	79	76	74	80	78	76	74	78	76	74	73	76	74	73	72	69
						7.0	82	81	79	77	81	80	78	77	79	78	77	75	77	76	75	74	72
						10.0	83	82	81	80	82	81	80	79	80	79	79	78	79	78	77	76	74

