

屋内照明器具特性	
品番 (品名)	L G B 1 6 4 0 1 K
光源	L D A 4 W W - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 8 7 0 3 0 (0) D B 1
B Z 分類	B Z 6

器具効率		9 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束 下方光束		2 8 % 7 0 %	室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 7	0 . 6	5 0	3 8	3 0	2 5	4 7	3 6	2 9	2 4	4 2	3 3	2 7	2 3	3 7	3 0	2 5	2 1	1 7		
			0 . 6 3	0 . 8	5 8	4 6	3 8	3 2	5 5	4 4	3 7	3 1	4 9	4 0	3 4	2 9	4 3	3 6	3 1	2 7	2 2		
			0 . 5 6	1 . 0	6 3	5 2	4 4	3 8	6 0	5 0	4 2	3 6	5 3	4 5	3 9	3 4	4 7	4 0	3 5	3 1	2 5		
				1 . 2 5	6 9	5 8	5 0	4 4	6 5	5 5	4 8	4 2	5 7	5 0	4 4	3 9	5 1	4 5	4 0	3 6	2 9		
下方投影面積		c m ²	1 . 5	7 2	6 2	5 5	4 9	6 8	5 9	5 2	4 7	6 1	5 4	4 8	4 3	5 4	4 8	4 3	3 9	3 2			
等価発光面積			c m ²	2 . 0	7 8	6 9	6 2	5 6	7 3	6 6	5 9	5 4	6 5	5 9	5 4	4 9	5 8	5 3	4 9	4 5	3 7		
取付高さ	器具間隔最大限			2 . 5	8 1	7 3	6 7	6 1	7 7	7 0	6 4	5 9	6 9	6 3	5 8	5 4	6 1	5 7	5 3	4 9	4 1		
			横方向 (A)	縦方向 (B)		3 . 0	8 4	7 7	7 1	6 6	7 9	7 3	6 8	6 3	7 1	6 6	6 2	5 8	6 3	5 9	5 6	5 2	4 4
H m		1 . 0 6 H m	1 . 0 6 H m	4 . 0	8 7	8 1	7 6	7 2	8 3	7 7	7 3	6 9	7 4	7 0	6 6	6 3	6 6	6 3	6 0	5 7	4 8		
				5 . 0	8 9	8 4	8 0	7 6	8 5	8 0	7 6	7 3	7 6	7 3	6 9	6 6	6 8	6 6	6 3	6 0	5 1		
				7 . 0	9 2	8 8	8 4	8 1	8 7	8 4	8 1	7 8	7 9	7 6	7 3	7 1	7 1	6 9	6 7	6 5	5 5		
				1 0 . 0	9 4	9 1	8 8	8 5	8 9	8 7	8 4	8 2	8 1	7 9	7 7	7 5	7 3	7 1	7 0	6 8	5 8		

