

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | LGB15455K                  |
| 光源       | LDA4L-H-E17/S/4 ×1 440.0lm |
| 管理番号     | K0164280(1)DB1             |
| BZ分類     | BZ6/0.7/BZ5                |

| 器具効率   |                     | 96 %            | 反射率    | 天井              | 80 %             |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|---------------------|-----------------|--------|-----------------|------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|        |                     |                 |        | 壁               | 70               | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |                     |                 |        | 床               | 10 %             |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |                     |                 |        | 室指数             | 照明率 ( X0.01) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率    |                     | 良<br>中<br>否     | 0.67   | 0.6             | 50               | 38 | 31 | 25 | 48   | 37 | 30 | 25 | 43   | 34 | 28 | 23 | 39   | 32 | 26 | 22 | 19  |
|        |                     |                 | 0.63   | 0.8             | 59               | 48 | 40 | 35 | 56   | 46 | 39 | 34 | 51   | 43 | 37 | 32 | 47   | 40 | 35 | 31 | 27  |
|        |                     |                 | 0.56   | 1.0             | 65               | 55 | 47 | 42 | 62   | 53 | 46 | 41 | 57   | 49 | 43 | 39 | 52   | 45 | 40 | 36 | 32  |
|        |                     |                 |        | 1.25            | 71               | 61 | 54 | 49 | 68   | 59 | 53 | 47 | 62   | 55 | 49 | 45 | 57   | 51 | 46 | 42 | 37  |
| 下方投影面積 |                     | cm <sup>2</sup> |        | 1.5             | 75               | 66 | 59 | 54 | 72   | 64 | 58 | 52 | 66   | 59 | 54 | 50 | 60   | 55 | 50 | 47 | 41  |
|        |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0              | 80 | 73 | 67 | 62   | 77 | 70 | 65 | 60   | 71 | 65 | 61 | 57   | 65 | 60 | 57 | 53  |
| 取付高さ   | 器具間隔最大限             |                 | 2.5    | 84              | 77               | 72 | 67 | 80 | 74   | 69 | 65 | 74 | 69   | 65 | 61 | 68 | 64   | 61 | 58 | 51 |     |
|        | 横方向 ( A ) 縦方向 ( B ) |                 |        | 3.0             | 86               | 80 | 75 | 71 | 83   | 77 | 73 | 69 | 76   | 72 | 68 | 65 | 70   | 67 | 64 | 61 | 54  |
| H m    | 1.48 H m            | 1.48 H m        | 4.0    | 89              | 84               | 80 | 77 | 86 | 81   | 78 | 74 | 79 | 76   | 73 | 70 | 73 | 70   | 68 | 65 | 58 |     |
|        |                     |                 | 5.0    | 91              | 87               | 83 | 80 | 87 | 84   | 81 | 78 | 81 | 78   | 75 | 73 | 75 | 72   | 70 | 68 | 61 |     |
|        |                     |                 | 7.0    | 93              | 90               | 87 | 85 | 90 | 87   | 84 | 82 | 83 | 81   | 79 | 77 | 77 | 75   | 73 | 72 | 64 |     |
|        |                     |                 | 10.0   | 95              | 93               | 90 | 88 | 91 | 89   | 87 | 86 | 85 | 83   | 82 | 80 | 79 | 77   | 76 | 75 | 67 |     |

