

| 屋内照明器具特性 |                                      |
|----------|--------------------------------------|
| 品番 (品名)  | L G B 1 6 7 3 4 K                    |
| 光源       | LDA4 L - H - E17 / S / 4 ×1 440.0 lm |
| 管理番号     | K0134190 ( 0 ) DB 1                  |
| B Z 分類   | B Z 5                                |

| 器具効率           |                     | 89 %                | 反射率             | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |   |   |
|----------------|---------------------|---------------------|-----------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|---|---|
|                |                     |                     |                 | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |   |   |
|                |                     |                     |                 | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |   |   |
| 上方光束           |                     | 0 %                 | 室指数             | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z  | C | M |
| 下方光束           |                     | 89 %                |                 |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |   |   |
| 保守率            |                     | 良<br>中<br>否         | 0.67            | 0.6           | 50   | 38 | 31 | 26 | 48   | 38 | 31 | 26 | 46   | 37 | 31 | 26 | 44   | 36 | 30 | 26 | 24  |    |   |   |
|                |                     |                     | 0.63            | 0.8           | 58   | 48 | 41 | 35 | 57   | 47 | 40 | 35 | 55   | 46 | 40 | 35 | 52   | 45 | 39 | 35 | 33  |    |   |   |
|                |                     |                     | 1.0             | 64            | 54   | 47 | 42 | 63 | 54   | 47 | 42 | 60 | 52   | 46 | 41 | 58 | 51   | 45 | 41 | 39 |     |    |   |   |
|                |                     |                     | 0.56            | 1.25          | 70   | 61 | 54 | 49 | 68   | 60 | 53 | 48 | 65   | 58 | 52 | 48 | 63   | 57 | 52 | 47 | 45  |    |   |   |
| 下方投影面積         |                     | cm <sup>2</sup>     | 1.5             | 74            | 65   | 59 | 54 | 72 | 64   | 58 | 53 | 69 | 63   | 57 | 53 | 66 | 61   | 56 | 52 | 50 |     |    |   |   |
| 等価発光面積         |                     |                     | cm <sup>2</sup> | 2.0           | 79   | 72 | 66 | 61 | 77   | 71 | 65 | 61 | 74   | 69 | 64 | 60 | 72   | 67 | 63 | 59 | 57  |    |   |   |
| 取付<br>高さ       | 器具間隔最大限             |                     | 2.5             | 82            | 76   | 71 | 66 | 81 | 75   | 70 | 66 | 78 | 73   | 69 | 65 | 75 | 71   | 67 | 64 | 62 |     |    |   |   |
|                | 横方向 ( A )           |                     | 縦方向 ( B )       |               | 3.0  | 84 | 79 | 74 | 70   | 83 | 78 | 74 | 70   | 80 | 76 | 72 | 69   | 77 | 74 | 71 | 68  | 66 |   |   |
| H <sub>m</sub> | 1.30 H <sub>m</sub> | 1.30 H <sub>m</sub> | 4.0             | 87            | 83   | 79 | 76 | 86 | 82   | 78 | 75 | 83 | 80   | 77 | 74 | 81 | 78   | 75 | 73 | 71 |     |    |   |   |
|                |                     |                     | 5.0             | 89            | 86   | 82 | 79 | 88 | 84   | 82 | 79 | 85 | 82   | 80 | 78 | 83 | 80   | 78 | 76 | 74 |     |    |   |   |
|                |                     |                     | 7.0             | 91            | 89   | 86 | 84 | 90 | 87   | 85 | 83 | 87 | 85   | 83 | 82 | 85 | 83   | 82 | 80 | 78 |     |    |   |   |
|                |                     |                     | 10.0            | 93            | 91   | 89 | 87 | 92 | 90   | 88 | 87 | 89 | 88   | 86 | 85 | 87 | 86   | 85 | 83 | 81 |     |    |   |   |

