

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 4 6
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 9 1 9 9 3 (0) D R 1
B Z 分類	B Z 1

器具効率			7 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束			7 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束																							
保守率			良 中 否	0 . 6	6 5	6 1	5 9	5 7	6 5	6 1	5 8	5 7	6 4	6 1	5 8	5 7	6 3	6 0	5 8	5 6	5 6		
				0 . 8	7 0	6 6	6 4	6 2	6 9	6 6	6 3	6 2	6 8	6 5	6 3	6 1	6 7	6 5	6 3	6 1	6 0		
				1 . 0	7 2	6 9	6 7	6 5	7 2	6 9	6 6	6 5	7 1	6 8	6 6	6 5	7 0	6 7	6 6	6 4	6 3		
				0 . 5 6	1 . 2 5	7 4	7 2	6 9	6 8	7 4	7 1	6 9	6 8	7 3	7 0	6 9	6 7	7 1	7 0	6 8	6 7	6 6	
下方投影面積			c m ²	1 . 5	7 6	7 3	7 1	7 0	7 5	7 3	7 1	7 0	7 4	7 2	7 0	6 9	7 3	7 1	7 0	6 9	6 7		
				等価発光面積			c m ²	2 . 0	7 8	7 6	7 4	7 2	7 7	7 5	7 3	7 2	7 5	7 4	7 3	7 1	7 4	7 3	7 2
取付 高さ	器具間隔最大限			2 . 5	7 9	7 7	7 5	7 4	7 8	7 6	7 5	7 4	7 6	7 5	7 4	7 3	7 5	7 4	7 3	7 2	7 1		
	横方向 (A)		縦方向 (B)	3 . 0	7 9	7 8	7 7	7 5	7 9	7 7	7 6	7 5	7 7	7 6	7 5	7 4	7 6	7 5	7 4	7 3	7 2		
H m	0 . 3 9 H m		0 . 3 9 H m	4 . 0	8 0	7 9	7 8	7 7	7 9	7 8	7 7	7 7	7 8	7 7	7 6	7 6	7 6	7 6	7 5	7 5	7 3		
				5 . 0	8 1	8 0	7 9	7 8	8 0	7 9	7 8	7 8	7 8	7 8	7 7	7 6	7 7	7 6	7 6	7 5	7 4		
				7 . 0	8 1	8 1	8 0	7 9	8 0	8 0	7 9	7 9	7 9	7 8	7 8	7 7	7 7	7 7	7 7	7 6	7 4		
				1 0 . 0	8 2	8 1	8 1	8 0	8 1	8 0	8 0	8 0	7 9	7 9	7 9	7 8	7 8	7 7	7 7	7 7	7 5		

