

屋内照明器具特性	
品番 (品名)	L G B 1 6 4 7 3
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0187731 (0) DB 1
B Z 分類	BZ5 / 1.1 / BZ4

器具効率		61 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	34	26	22	18	33	26	21	18	32	25	21	18	30	25	21	18	17
			0.63	0.8	40	33	29	25	39	33	28	25	38	32	28	25	36	31	28	25	23
			0.56	1.0	45	38	34	30	44	38	33	30	42	37	33	30	40	36	32	30	28
				1.25	49	43	39	35	48	42	38	35	46	41	38	35	44	40	37	34	33
下方投影面積 等価発光面積		cm ²		1.5	51	46	42	39	50	46	42	39	49	44	41	38	47	43	40	38	37
				2.0	55	51	47	44	54	50	47	44	52	49	46	44	50	48	45	43	42
				2.5	57	54	51	48	56	53	50	48	54	52	49	47	53	50	48	47	45
取付 高さ	器具間隔最大限			3.0	59	55	53	51	58	55	52	50	56	54	51	50	54	52	51	49	47
	横方向 (A)	縦方向 (B)		4.0	60	58	56	54	59	57	55	54	58	56	54	53	56	55	53	52	50
H m	1.35 H m	1.35 H m		5.0	61	59	58	56	61	59	57	56	59	57	56	55	57	56	55	54	52
				7.0	63	61	60	59	62	61	59	58	60	59	58	57	59	58	57	56	55
				10.0	64	63	62	61	63	62	61	60	61	60	60	59	60	59	59	58	56

