

屋内照明器具特性	
品番 (品名)	P M L L 1 1 0 9 4 K 2 7
光源	LED2700_70_1040 x1 1040.0 lm
管理番号	K0178297(0)DY1
BZ分類	BZ5/0.7/BZ4/2.8/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	92%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	57	45	37	32	55	44	37	32	52	42	36	31	49	41	35	31	28
	中	0.67	0.8	67	56	48	42	65	54	47	42	61	52	46	41	58	50	45	40	38
	否	0.63	1.0	73	63	55	50	71	62	55	49	67	59	53	48	64	57	51	47	44
			1.25	79	70	63	57	77	68	62	56	73	65	60	55	69	63	58	54	51
下方投影面積	c m ²		1.5	83	74	68	63	81	73	67	62	76	70	65	60	73	67	63	59	55
	等価発光面積		c m ²	2.0	88	81	75	71	86	79	74	70	82	76	72	68	78	73	69	66
取付高さ	器具間隔最大限		2.5	92	85	80	76	89	84	79	75	85	80	76	73	81	77	74	71	67
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	92	87	82	79	87	83	80	76	83	80	77	74	70
1.5m	1.91m	2.08m	4.0	97	93	89	85	95	91	87	84	90	87	84	81	86	84	81	79	74
2	2.53	2.65	5.0	99	95	92	89	96	93	90	88	92	89	87	85	88	86	84	82	77
2.5	3.15	3.23	7.0	101	98	96	93	99	96	94	92	94	92	90	89	90	89	87	86	81
3	3.76	3.84	10.0	102	100	99	97	100	98	97	95	96	95	93	92	92	91	90	89	84

