

# 屋内照明器具特性

品番 (品名)	NCN25301S	
光源	LED4000_85_2090 x1 2090.0lm	
管理番号	K0177434(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.81	0.6	80	73	68	65	79	72	68	65	77	71	68	65	76	71	67	65	63	
	中 0.77		0.8	87	81	77	74	86	81	77	74	85	80	76	73	83	79	76	73	72
	否 0.68		1.0	92	86	82	79	91	86	82	79	89	85	81	79	87	84	81	78	77
下方投影面積	cm <sup>2</sup>	1.25	95	91	87	84	94	90	87	84	92	89	86	83	91	88	85	83	81	
		1.5	98	93	90	88	97	93	90	87	95	91	89	87	93	90	88	86	84	
等価発光面積	cm <sup>2</sup>	2.0	101	97	94	92	99	96	94	92	97	95	93	91	96	93	92	90	88	
		2.5	102	99	97	95	101	99	96	94	99	97	95	93	97	95	94	92	90	
取付高さ	器具間隔最大限		3.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92
	横方向 (A)	縦方向 (B)	4.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	96	94
Hm	0.64Hm	0.64Hm	5.0	106	104	103	101	104	103	102	101	102	101	100	99	100	99	98	98	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	99	97
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98

