

屋内照明器具特性

品番 (品名)	L G W J 5 6 9 7 5 F																
光源	LDA4L - G / S / K4 ×1 485.0 l m																
管理番号	K0134339 (0) DR 1																
BZ分類	BZ10																

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束 下方光束	44 % 24 %	反射率	室指数																	
保守率	良 中 否	0.63 0.6 0.56	照明率 (X0.01) ZCM																	
			0.6	2.9	2.1	1.6	1.2	2.6	1.9	1.4	1.1	2.0	1.5	1.1	8	1.5	1.1	8	6	2
下方投影面積 等価発光面積	c m ² c m ²	1.25 1.5 2.0	0.6	2.9	2.1	1.6	1.2	2.6	1.9	1.4	1.1	2.0	1.5	1.1	8	1.5	1.1	8	6	2
			2.5	4.2	3.5	2.9	2.5	3.8	3.1	2.6	2.2	2.9	2.4	2.1	1.8	1.5	2.0	1.6	1.3	1.1
取付 高さ	器具間隔最大限		3.0	4.2	3.5	2.9	2.5	3.8	3.1	2.6	2.2	2.9	2.4	2.1	1.8	1.5	2.0	1.6	1.3	1.1
	横方向 (A)	縦方向 (B)	4.0	4.5	3.8	3.3	2.8	4.0	3.4	2.9	2.6	3.1	2.7	2.3	2.0	2.3	2.0	1.7	1.5	6
H m	0.00 H m	0.00 H m	2.0	4.9	4.3	3.8	3.3	4.4	3.8	3.4	3.0	3.4	3.0	2.7	2.4	2.5	2.2	2.0	1.8	8
			2.5	5.1	4.6	4.1	3.7	4.6	4.1	3.7	3.4	3.6	3.3	3.0	2.7	2.7	2.4	2.2	2.0	10
			3.0	5.3	4.8	4.4	4.0	4.8	4.3	4.0	3.6	3.8	3.4	3.2	2.9	2.8	2.6	2.4	2.2	11
			4.0	5.5	5.1	4.8	4.4	5.0	4.6	4.3	4.0	4.0	3.7	3.4	3.2	3.0	2.8	2.6	2.4	13
			5.0	5.7	5.3	5.0	4.7	5.1	4.8	4.5	4.3	4.1	3.9	3.6	3.4	3.1	2.9	2.8	2.6	14
			7.0	5.8	5.6	5.3	5.1	5.3	5.1	4.8	4.6	4.2	4.1	3.9	3.7	3.3	3.1	3.0	2.9	16
			10.0	6.0	5.8	5.6	5.4	5.4	5.3	5.1	4.9	4.4	4.2	4.1	4.0	3.4	3.3	3.2	3.1	17

