

屋内照明器具特性	
品番 (品名)	L G W C 8 5 2 1 8 F
光源	L D A 4 L - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 6 8 5 8 9 (0) D B 1
B Z 分類	B Z 7 / 0 . 7 / B Z 8 / 4 . 5 / B Z 7

器具効率		5 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 3	0 . 6	2 6	1 9	1 5	1 2	2 5	1 8	1 4	1 1	2 2	1 7	1 3	1 0	2 0	1 5	1 2	1 0	8
			0 . 6	0 . 8	3 0	2 3	1 8	1 5	2 8	2 2	1 7	1 4	2 5	2 0	1 6	1 3	2 2	1 8	1 4	1 2	9
			0 . 5 6	1 . 0	3 3	2 6	2 1	1 7	3 1	2 5	2 0	1 7	2 8	2 2	1 8	1 5	2 4	2 0	1 7	1 4	1 1
				1 . 2 5	3 6	2 9	2 4	2 0	3 4	2 8	2 3	2 0	3 0	2 5	2 1	1 8	2 6	2 2	1 9	1 6	1 3
下方投影面積		c m ²	1 . 5	3 8	3 2	2 7	2 3	3 6	3 0	2 6	2 2	3 2	2 7	2 4	2 0	2 8	2 4	2 1	1 9	1 5	
			等価発光面積	c m ²	2 . 0	4 1	3 6	3 1	2 8	3 9	3 4	3 0	2 7	3 5	3 1	2 7	2 4	3 1	2 8	2 5	2 2
取付 高さ	器具間隔最大限		2 . 5	4 4	3 9	3 5	3 1	4 1	3 7	3 3	3 0	3 7	3 3	3 0	2 7	3 3	3 0	2 8	2 5	2 1	
	横方向 (A) 縦方向 (B)		3 . 0	4 5	4 1	3 7	3 4	4 3	3 9	3 6	3 2	3 9	3 5	3 2	3 0	3 5	3 2	3 0	2 7	2 3	
H m	0 . 6 5 H m 0 . 6 6 H m		4 . 0	4 7	4 4	4 1	3 8	4 5	4 2	3 9	3 6	4 1	3 8	3 6	3 3	3 7	3 5	3 3	3 1	2 6	
			5 . 0	4 9	4 6	4 3	4 0	4 7	4 4	4 1	3 9	4 2	4 0	3 8	3 6	3 8	3 6	3 5	3 3	2 8	
			7 . 0	5 1	4 8	4 6	4 4	4 8	4 6	4 4	4 2	4 4	4 2	4 1	3 9	4 0	3 9	3 7	3 6	3 1	
			1 0 . 0	5 2	5 0	4 8	4 7	5 0	4 8	4 7	4 5	4 6	4 4	4 3	4 2	4 2	4 0	3 9	3 8	3 3	

