

屋内照明器具特性

品番 (品名)	P M L E L 0 7 2 5 0 N C									
光源	LED5000_70_1910 x1					1910.0 1 m				
管理番号	K0177199 (0) DY 1									
B Z 分類	B Z 2 / 0 . 9 / B Z 3 / 6 . 0 / B Z 4									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 5 %		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
下方光束 95 %	室指数	照明率 (X 0 . 0 1)																Z C M			
保守率	良	0.69	0.6	66	56	50	45	65	55	49	45	62	54	49	45	60	53	48	44	42	
	中	0.67	0.8	74	65	59	54	73	64	59	54	70	63	58	54	68	61	57	53	51	
	否	0.63	1.0	80	72	65	61	78	71	65	60	75	69	64	60	72	67	62	59	57	
			1.25	85	77	71	67	83	76	71	66	80	74	69	65	77	72	68	64	62	
下方投影面積			1.5	88	81	76	71	86	80	75	71	83	78	73	70	80	75	72	68	66	
	等価発光面積		2.0	92	87	82	78	91	85	81	77	87	83	79	76	84	80	77	74	71	
取付高さ	器具間隔最大限		2.5	95	90	86	82	93	89	85	81	90	86	83	80	86	83	81	78	75	
	横方向 (A)	縦方向 (B)	3.0	97	93	89	85	95	91	88	85	92	88	85	83	88	86	83	81	77	
1.5m	1.04 m	1.77 m	4.0	99	96	93	90	97	94	91	89	94	91	89	87	91	88	86	85	81	
2	1.37	2.3	5.0	101	98	95	93	99	96	94	92	95	93	91	89	92	90	89	87	83	
2.5	1.71	2.85	7.0	103	100	98	96	101	99	97	95	97	96	94	92	94	93	91	90	86	
3	2.04	3.4	10.0	104	102	101	99	102	101	99	98	99	97	96	95	95	94	93	92	88	

