

屋内照明器具特性	
品番 (品名)	XAD3 4 4 0 V
光源	LLD4000VCE1 ×1 845.0 l m
管理番号	K0175553 (0) DR 1
BZ分類	BZ5

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	47	37	31	26	46	37	31	26	44	36	30	26	43	35	30	26	25
			0.63	0.8	56	46	40	35	54	46	40	35	52	45	39	35	50	43	38	35	33
			0.56	1.0	61	52	46	41	60	52	46	41	57	50	45	41	55	49	44	41	39
				1.25	66	58	52	48	65	57	52	47	62	56	51	47	60	55	50	47	45
下方投影面積		cm ²		1.5	70	62	57	52	68	62	56	52	66	60	55	52	63	58	54	51	49
			等価発光面積	cm ²	2.0	74	68	63	59	73	67	63	59	70	66	62	58	68	64	61	58
取付高さ	器具間隔最大限			2.5	77	72	68	64	76	71	67	64	73	69	66	63	71	68	65	62	60
	横方向 (A) 縦方向 (B)			3.0	79	75	71	67	78	74	70	67	75	72	69	66	73	70	68	65	63
H m	1.25 H m	1.25 H m		4.0	82	78	75	72	80	77	74	72	78	75	73	71	76	74	72	70	67
				5.0	83	80	78	75	82	79	77	75	80	78	75	74	78	76	74	72	70
				7.0	85	83	81	79	84	82	80	78	82	80	79	77	80	78	77	76	73
				10.0	86	85	83	82	85	84	83	81	83	82	81	80	81	80	79	78	76

