

屋内照明器具特性	
品番 (品名)	XAD3 4 4 1 L
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0175551 (0) DR 1
BZ分類	BZ5

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	43	34	28	24	42	33	28	24	40	32	27	24	38	32	27	23	22
			0.63	0.8	50	42	36	32	49	41	36	31	47	40	35	31	45	39	35	31	30
			0.56	1.0	55	47	41	37	54	47	41	37	52	45	41	37	50	44	40	37	35
				1.25	60	52	47	43	58	52	47	43	56	50	46	42	54	49	45	42	40
下方投影面積 等価発光面積		cm ² cm ²		1.5	63	56	51	47	61	55	51	47	59	54	50	46	57	53	49	46	44
				2.0	67	61	57	53	66	61	56	53	63	59	55	52	61	58	54	52	50
				2.5	69	65	61	58	68	64	60	57	66	62	59	56	64	61	58	56	54
				3.0	71	67	64	61	70	66	63	60	68	65	62	59	66	63	61	59	57
H m	1.25 H m	1.25 H m		4.0	74	70	68	65	72	69	67	65	70	68	66	64	68	66	64	63	61
				5.0	75	72	70	68	74	71	69	67	72	70	68	66	70	68	67	65	63
				7.0	77	75	73	71	76	74	72	70	74	72	71	69	72	70	69	68	66
				10.0	78	76	75	74	77	75	74	73	75	74	73	72	73	72	71	70	68

