

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNN33000W                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_1940 x1 1940.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0177078(0)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ2/8.5/BZ1                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |              |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |    |
|--------|------------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|
| 器具効率   | 100%             | 天井      | 80%          |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0%  |    |    |
|        |                  |         | 反射率          | 壁   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30  | 10 | 0% |
|        |                  |         |              | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |     |    | 0% |
| 上方光束   | 0%               | 室指数     | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |    |    |
| 下方光束   | 100%             |         |              |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |    |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6          | 68  | 58  | 52  | 48  | 67  | 58  | 52  | 48  | 65  | 57  | 52  | 48  | 63  | 56  | 51 | 47  | 46 |    |
|        |                  | 0.77    | 0.8          | 78  | 69  | 64  | 59  | 77  | 69  | 63  | 59  | 75  | 68  | 63  | 59  | 73  | 67  | 62 | 59  | 57 |    |
|        |                  |         | 1.0          | 84  | 77  | 71  | 67  | 83  | 76  | 71  | 67  | 81  | 75  | 70  | 67  | 79  | 73  | 69 | 66  | 65 |    |
|        |                  | 0.68    | 1.25         | 89  | 83  | 78  | 74  | 88  | 82  | 77  | 74  | 86  | 80  | 76  | 73  | 84  | 79  | 76 | 73  | 71 |    |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 92           | 87  | 82  | 78  | 91  | 86  | 82  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 77 | 75  |    |    |
|        |                  | 2.0     | 97           | 92  | 88  | 85  | 95  | 91  | 87  | 84  | 93  | 89  | 86  | 84  | 91  | 88  | 85  | 83 | 81  |    |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5          | 99  | 95  | 92  | 89  | 98  | 94  | 91  | 88  | 95  | 92  | 90  | 87  | 93  | 91  | 88 | 86  | 84 |    |
|        | 横方向 (A)          | 縦方向 (B) | 3.0          | 101 | 97  | 94  | 92  | 99  | 96  | 94  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91 | 89  | 87 |    |
| 1.5m   | 1.7m             | 1.88m   | 4.0          | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 95  | 94 | 92  | 90 |    |
| 2      | 2.25             | 2.34    | 5.0          | 104 | 102 | 100 | 98  | 102 | 101 | 99  | 97  | 100 | 99  | 97  | 96  | 98  | 97  | 95 | 94  | 92 |    |
| 2.5    | 2.81             | 2.82    | 7.0          | 105 | 103 | 102 | 101 | 104 | 102 | 101 | 100 | 102 | 100 | 99  | 98  | 99  | 98  | 97 | 97  | 94 |    |
| 3      | 3.35             | 3.32    | 10.0         | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 102 | 102 | 101 | 100 | 100 | 99  | 98 | 98  | 96 |    |

