

# 屋内照明器具特性

品番 (品名)	LGB81822														
光源	LED2700_70_2165 x1 2165.0 1m														
管理番号	K0142374(0)DR1														
BZ分類	BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	50%	反射率	床	10%				10%				10%				10%				0%
下方光束	50%		室指数	照明率 ( X0.01) ZCM																
保守率	良 中 否 0.67 0.63 0.56	0.6	48	36	29	23	44	34	27	22	37	29	23	19	30	24	20	16	11	
		0.8	56	45	37	32	52	42	35	30	43	36	30	26	36	30	25	22	16	
		1.0	62	52	44	38	57	48	41	36	48	41	35	31	40	34	30	26	19	
		1.25	68	58	50	45	62	54	47	42	52	46	41	36	43	38	34	31	22	
下方投影面積	c m <sup>2</sup>	1.5	72	63	55	50	66	58	52	47	56	49	44	40	46	41	37	34	24	
		2.0	77	69	63	57	71	64	59	54	60	55	50	46	50	46	42	39	28	
取付高さ	器具間隔最大限		2.5	81	74	68	63	74	68	63	59	63	58	54	51	52	49	46	31	
	横方向 (A)	縦方向 (B)	3.0	83	77	72	67	77	71	67	63	65	61	57	54	54	51	48	33	
1.5m	1.25m	2.19m	4.0	86	81	77	73	80	75	71	68	68	64	61	59	56	54	36		
2	1.67	2.77	5.0	88	84	80	77	82	78	75	71	69	67	64	62	58	56	38		
2.5	2.08	3.38	7.0	90	87	84	81	84	81	78	76	72	69	67	65	60	58	40		
3	2.5	4.01	10.0	92	90	88	85	86	84	82	80	73	72	70	69	62	60	42		

